

Dynapac CC2200C

Combi rollers

Atlas Copco



Technical data



Masses

Max. operating mass	18,100 lbs
Operating mass (incl. ROPS)	16,300 lbs
Module mass (front/rear)	8,500/7,800 lbs



Propulsion

Speed range	0-7,5 mph
Vertical oscillation	±7
Theor. gradeability	49 %



Compaction

Wheel load	1.950 (pounds/wheel)
Centrifugal force (high/low amplitude)	17,540/15,060 lb
Nominal amplitude (high/low)	0.028/0.012 in
Static linear load	144 lbs/in
Vibration frequency (high/low amplitude)	2,880/4,020 vpm
Water tank	198 gal
Emulsion tank	21 gal



Engine

Manufacturer/Model	Deutz TCD 3.6 T4i
Rated power, SAE J1995	74 kW (100 hp) @ 2,200 rpm
Fuel tank capacity	34 gal



Hydraulic system

Driving	Axial piston pump with variable displacement. Axial piston motors (3) with variable displacement.
Vibration	Axial piston pump with variable displacement. Axial piston motor with constant displacement.
Steering	Gear pump with constant displacement.
Service brake	Hydrostatic in forward and reverse lever.
Parking/Emergency brake	Failsafe multidisc brake in both drums.

Find us locally at www.atlascopco.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.


rce_cc2200c_us-20140515.084840.pdf 2014-05-15 08:48

Dynapac CC2200C

Combi rollers

Atlas Copco

Technical data



Dimensions

A. Wheelbase	131 in
B. Width	64 in
C. Curb clearance	28 in
D. Drum diameter	45 in
H1. Height, with ROPS/cab	118 in
H2. Height, w/o ROPS/cab	90 in
K. Ground clearance	11 in
L. Length	177 in
R. Turning radius, outside	206 in
S. Drum shell thickness	0.7 in
W1. Drum width	59 in
W2. Width, wheel module	57 in
W3. Width, tyre	11 in
W4. Wheel track	17 in
W5. Wheel spacing	3 in
α. Steering angle	±32°



Standard equipment

- Automatic vibration control (AVC)
- Automatic water control (AWC)
- Back-up alarm
- Display: Engine temp, Fuel level, Frequency/impactometer, Hydr. temp, Speedometer, Tachometer, Voltage, VPM, Water level
- Filters for sprinkler system
- Hydraulic check points
- Lunch box holder
- Operator platform, shock mounted
- Pressurized sprinkler system
- ROPS canopy w/suspension seat & 3" seat belt
- Rotating beacon
- Sliding and swiveling operator's platform
- Spring loaded scrapers
- Sprinkler timer
- Sprinkler system additional (Two bars per drum)
- Steering wheel tilt able
- Vandal cover for instrument panel
- Vibration quick stop
- Vibration shut off front or rear drum
- Warning lights: Air cleaner, Brake, Clogged hyd. fluid filter, Engine oil pressure/temp, Hyd oil temp, Low charge, Low fuel
- Working lights, Rops mounted



Optional equipment

- Asphalt Temp Meter
- Compaction Analyzer
- Drum Edge Lights
- Whisper Cab Package

Find us locally at www.atlascopco.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.

rce_cc2200c_us-20140515.084840.pdf 2014-05-15 08:48